

SUPREME

997J-011 S3S SC FO SR

STANDARD EN ISO 20345:2022

SIZES 38-48

Three-dimensional **SPYDER-NET**: lining with moisture absorption and release properties. Its special three-dimensional structure provides exceptional shape memory and high snag-resistance

Dual density **HYBRID PU/PU** sole made from high-density polyurethane injected with low-density polyurethane midsole. The remarkably antistatic polyurethane sole offers excellent slip and oil resistance and guarantees maximum flexibility



Dual density HYBRID PU/PU

- Enhanced non-slip lugs for extreme grip
- Wide sole for maximum protection and robustness
- Sole profiling for maximum ground grip



SUPREMOIL highly breathable full-grain leather, extremely soft, resistant to water, oils and hydrocarbons

X-LEATHER multi-layer polyurethane reinforced material with high abrasion resistance properties and excellent water and oil resistance

COMPO200 composite toe cap and **TXZERO STRONG** anti-puncture insole made of high tenacity fibers to obtain a flexible textile that adapts to movement of the foot; it is intrinsically antistatic



T-01

- Anatomical insole for increased comfort
- High-density foam = energy absorption and rebound
- Lining made from conductive micro-perforated fabric to reduce wear and tear



A - Antistatic



PS - Non-metal anti-perforation insert (truncated cone nail)



E - Energy absorption in the heel region



FO - Sole resistant to hydrocarbons



Toecap resistant up to an impact of 200 joules and crushing of 15 KN



SC - abrasion resistant overcap



WPA - Upper resistant to water penetration and absorption



SR - Slip resistance on ceramic tile with glycerin



Metal free

Esolight 1.0 polyurethane midsole. The low-density polyurethane microcells enhance energy absorption ensuring comfort and lightness