

AMAZONAS PK 170

326R-012 S3S SC CI FO SR ESD

STANDARD EN ISO 20345:2022

SIZES 36-48



Three-dimensional **SPYDER-NET**: lining with moisture absorption and release properties. Its special three-dimensional structure provides exceptional shape memory and high snag-resistance

DNX SYSTEM: ergonomic protection system made from a specially reinforced TPU, with anti-shock function

Midsole in soft polyurethane, ultralight and flexible, functional heel design to offer comfort while walking and guarantee energy absorption in the heel region

PU-Tek: breathable, water and abrasion-resistant fabric

Supplementary anti-abrasion (SC), impact and stain resistant TPU protection elements

	A - Antistatic
	PS - Non-metal anti-perforation insert (truncated cone nail)
	E - Energy absorption in the heel region
	FO - Sole resistant to hydrocarbons
	Toecap resistant up to an impact of 200 joules and crushing of 15 kN
	SC - abrasion resistant overcap
	WPA - Upper resistant to water penetration and absorption
	CI - Cold insulation of the sole
	SR - Slip resistance on ceramic tile with glycerin

The TPU outsole is remarkably antistatic, exceeding the requirements of EN ISO 20345:2022; it guarantees grip while walking. Thanks to the homogeneous distribution of the contact areas, the sole is suitable to all terrains

ALU200 aluminium toe cap and **TXZERO STRONG** anti puncture insole made of high tenacity fibers to obtain a flexible textile that adapts to the movement of the foot; it is intrinsically antistatic

Bi-component REBOUND PU/TPU

- Ultra-lightweight and high flexibility
- Shock-absorbing heel
- Differentiated depth grooves for enhanced comfort and shock absorbing heel

B-01

- Anatomical insole made of polyurethane compound for improved comfort
- TPE charge system for an even distribution of energy
- Lining with through-holes to increase air circulation

